

## 2252-73

# Remote Focus 4MP IP Camera



### Key Vaule Highlight

#### - High definition image detail

Users can zoom in the 2252-73 camera remotely to get the best view of the interested area. Allocate all 4 megapixel to a specific area can make the image extremely clear.

#### - Next Level Codec

The 2252-73 camera is able to deliver H.265 codec with 30% ~ 50% storage space saving on the NVR.

#### - Night vision

The 2252-73 camera can capture clear image at night with its built-in infrared LEDs.

#### - Simple setup.

Users only need single cable to carry the power and network to the camera. The power will be separated from the network cable with POE function.

#### - Efficient recording

Users can enable the motion detection to trigger footage recording when people walk in. They only need to review the motion footage to locate the person of interests. Pre-record capability makes sure the detail will not be missing.

### Typical Application

Headquarter office

Hotel

Logistics Center

Retail

convenience store

and others

## Specification

### Power

Input voltage	+12 VDC or Power-over-Ethernet
Power consumption	6 W (max)

### Video

Sensor type	1/3 Type CMOS Sensor
Sensor pixels	2592*1520
Sensitivity	0.5 lx (IR off) 0 lx (IR on)
Main-stream Resolution	2592*1520@15fps; 2048*1536@23fps
Sub-stream Resolution	4CIF@25fps; CIF@25fps
Video compression	H.265/H.264 MP (Main Profile)
DWDR	ON/OFF
3D DNR	Yes

### Night vision

Distance	30 m
LED	30 LED high efficiency array, 850 nm

### Lens

Lens type	Motorized 2.8 to 12 mm, Fixed Iris F1.4
Field of View	H: 85°- 26°
Lens mount	Board mounted
Day & Night	Auto ICR Switch (IR correction filter)

### Connection

Alarm input (optional)	1 alarm in
Alarm out (optional)	1 alarm out

### Audio (optional)

Audio input	RCA jack connector
Audio output	RCA jack connector
Audio communication	Two-way, full duplex
Audio compression	G.711 (live and recording)

### Local Storage (optional)

Memory card slot	Supports up to 128 GB micro SD card (An SD card of Class 10 or higher is recommended for HD recording)
Recording	Continuous recording, Motion/schedule recording

### Software Control

Unit configuration	Via web browser or PC surveillance software
--------------------	---

### Network

Protocols	HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x
Ethernet	10/100 Base-T, auto-sensing, half/full duplex, RJ45
Wireless	N/A
PoE	IEEE 802.3af compliant

### Mechanical

Dimensions	Diameter: 150 mm Height: 130mm
Weight	TBA

### Environmental

Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)

### Ordering Information

IR IP Dome MF 2.8~12mm lens	2252-73
--------------------------------	---------

\* Local Storage function is optional