

2291

Full HD PoE Box Camera



Key Vaule Highlight

- Color night-vision Image

The 2291 camera can deliver color night-vision image with extra detail in the low light condition.

- High definition image detail

The user can install 2291 box camera on location far away from surveillance point with its optional 10X optical zoom lens

- Heavy-duty Housing

The users can deploy a heavy-duty housing with 2291 box camera to stand the harsh environment outside perimeter, such as heavy wind, rain, and snow.

- Deterrence

The 2291 camera can generate deterrence for the criminal with heavy-duty housing.

- Simple and professional setup.

The users can easily test 2291 camera on the field. POE function allows single cable to carry the power and network to the camera.

Typical Application

Headquarter office
Campuses
Hotel
City Surveillance
Telecom
Logistics Center
and others

Specification

| Power | |
|--------------------------|---|
| Input voltage | +12 VDC or Power-over-Ethernet |
| Power consumption | 4.5 W (max) |
| Video | |
| Sensor type | 1/2.8 Type SONY Exmor CMOS Sensor |
| Sensor pixels | 1920x1080 |
| Sensitivity | 0.01 lx |
| Main-stream Resolution | 1920x1080 @25fps; 1280*720@25fps |
| Sub-stream Resolution | 4CIF@25fps; CIF@25fps |
| Video compression | H.264 MP (Main Profile) |
| DWDR | On/Off |
| 3D DNR | Yes |
| Lens | |
| Lens type | Varifocal 2.8 to 12 mm, Fixed Iris F1.4 (5*50mm is optional) |
| Field of View | H: 85°- 26° |
| Lens mount | CS mounted |
| Day & Night | Auto ICR Switch |
| Connection | |
| Analog video out | N/A |
| Alarm input (optional) | 1 alarm in |
| Alarm out (optional) | N/A |
| Audio (optional) | |
| Audio input | RCA jack connector |
| Audio output | RCA jack connector |
| Audio communication | Two-way, full duplex |
| Audio compression | G.711 (live and recording) |
| Local Storage (optional) | |
| Memory card slot | N/A |

| Software Control | |
|------------------------------|---|
| Unit configuration | Via web browser or PC surveillance software |
| Network | |
| Protocols | HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x |
| Ethernet | 10/100 Base-T, auto-sensing, half/full duplex, RJ45 |
| Wireless | N/A |
| PoE | IEEE 802.3af compliant |
| Mechanical | |
| Dimensions | 148*78*56mm (without lens) |
| Weight | TBA |
| Environmental | |
| Operating temperature Camera | -20 °C to +55 °C (-4 °F to +131 °F) |
| Storage temperature | -20 °C to +70 °C (-4 °F to +158 °F) |
| Humidity | 10% to 80% relative humidity (non condensing) |
| Ordering Information | |
| IP Box VF 2.8 to 12mm lens | 2291 |