

2545-15

Full HD PoE Panoramic Camera



Key Vaule Highlight

- Eye-level Setup

The user can install 2545-15 camera on the wall to an eye-evel position to capture the face detail.

- Panoramic view

The 2545-15 camera can deliver 180° Panoramic View and 360° Surround View with its built-in dewarppped engine.

- Working with regular NVR

The 2545-15 camera can work with regular NVR to record the dewarppped image.

- Flexible Coverage

The user can deploy single 2545-15 camera to cover multiple surveillance points.

- Simple setup.

Users only need single cable to carry the power and network to the camera. The power will be separated from the network cable with POE function.

Typical Application

Headquarter office

Hotel

Logistics Center

Retail

convenience store

and others

Specification

| Power | |
|--------------------------|---|
| Input voltage | +12 VDC or Power-over-Ethernet |
| Power consumption | 4.5 W (max) |
| Video | |
| Sensor type | 1/3-inch CMOS |
| Sensor pixels | 2048x1536 |
| Sensitivity | 0.5 lx (IR off) |
| Main-stream Resolution | 1920*1080 @20fps (Dewarped) |
| Sub-stream Resolution | 4CIF@20fps; CIF@25fps |
| Video compression | H.264 MP (Main Profile) |
| DWDR | On/Off |
| 3D DNR | Yes |
| Night vision | |
| Infrared LEDs | N/A |
| Lens | |
| Lens type | 1.42 mm |
| Field of View | 360° or 180° |
| Lens mount | Board mounted |
| Day & Night | Auto ICR Switch (IR correction filter) |
| Connection | |
| Alarm input (optional) | 1 alarm in |
| Alarm out (optional) | N/A |
| Audio (optional) | |
| Audio input | RCA jack connector |
| Audio output | RCA jack connector |
| Audio communication | Two-way, full duplex |
| Audio compression | G.711 (live and recording) |
| Local Storage (optional) | |
| Memory card slot | Supports up to 128 GB micro SD card (An SD card of Class 10 or higher is recommended for HD recording) |
| Recording | Continuous recording, Motion/schedule recording |

| Software Control | |
|------------------------------|---|
| Unit configuration | Via web browser or PC surveillance software |
| Network | |
| Protocols | HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x |
| Ethernet | 10/100 Base-T, auto-sensing, half/full duplex, RJ45 |
| Wireless | N/A |
| PoE | IEEE 802.3af compliant |
| Mechanical | |
| Dimensions | Diameter: 120 mm Height: 54 mm |
| Weight | TBA |
| Environmental | |
| Operating temperature Camera | -20 °C to +55 °C (-4 °F to +131 °F) |
| Storage temperature | -20 °C to +70 °C (-4 °F to +158 °F) |
| Humidity | 10% to 80% relative humidity (non condensing) |
| Ordering Information | |
| FishEye IP Dome, 1.19mm lens | 2545-15 |

* Local Storage function is optional