

2645-48

IP Height Strip Camera



Key Vaule Highlight

- Eye-level Setup

The user can install 2645-48 height strip camera on the door frame to capture the face detail.

- HD Image Detail

The 2645-48 height strip camera can provide image detailed in 2MP HD resolution with its 1/2.8 inch CMOS sensor.

- Covert Design

The discreet design make the camera easy to blend into business environment. The customer will more feel comfortable without seeing the camera shooting on them.

- All-in-one camera system

Users can choose either deploying heigh strip camera standalone or add the camera to the existed surveillance system. The footage can be recorded in the TF card inside the camera. Users don't need to take off memory card to retrieve the footage, They can access the camera remotely over the network connection.

- Simple setup.

Users only need single cable to carry the power and network to the 2645-48 height strip camera. The power will be separated from the network cable with POE function.

Typical Application

Retail

Convenience Store

Workshop

Logistics center

and others

Specification

Power

Input voltage	+12 VDC or Power-over-Ethernet
Power consumption	4.5 W (max)

Video

Sensor type	1/2.8 Type CMOS Sensor
Sensor pixels	1920x1080
Sensitivity	1.0 lx (IR off)
Main-stream Resolution	1920x1080@25fps; 1280x720@25fps
Sub-stream Resolution	4CIF@25fps; CIF@25fps
Video compression	H.264 MP (Main Profile)
DWDR	ON/OFF
3D DNR	Yes

Lens

Lens type	3.7 mm pinhole lens
Field of View	H: 77°
Lens mount	Board mounted
Day & Night	Auto IR Cut filter

Connection

Analog video out	N/A
Alarm input (optional)	1 alarm in
Alarm out (optional)	1 alarm out

Audio (optional)

Audio input	RCA jack connector
Audio output	RCA jack connector
Audio communication	Two-way, full duplex
Audio compression	G.711 (live and recording)

Local Storage (optional)

Memory card slot	Supports up to 128 GB micro SD card (An SD card of Class 8 or higher is recommended for HD recording)
Recording	Continuous recording, Motion/schedule recording

Software Control

Unit configuration	Via web browser or PC surveillance software
--------------------	---

Network

Protocols	HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x
Ethernet	10/100 Base-T, auto-sensing, half/full duplex, RJ45
Wireless	N/A
PoE	IEEE802.3af

Mechanical

Dimensions	870*52*38mm
Weight	TBA

Environmental

Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)

Ordering Information

IP Height Strip Camera	2645-48
------------------------	---------

Guangzhou

No.3 East Alley, Guangfeng East Road,
Zengchen District, Guangzhou., 511300,
P.R.China
Tel: +86-20-8244-2660
Fax: +86-20-8274-5925
Email: sales@golbong.com

Shenzhen

1/F Block 295, Jiuwei, Xixiang Town,
Baoan District, Shenzhen, 518000,
P.R.China
Tel: +86-755-81465995
Fax: +86-755-81469770
Email: sales@golbong.com