

## 2646-62

# WIFI Door frame Camera



### Key Vaule Highlight

#### - Face Capture Setup

The user can install 2646-62 camera on the door frame to capture the face detail.

#### - HD Image Detail

The 2646-62 IP door frame camera can provide image detailed in 1.3MP HD resolution with its 1/3 inch CMOS sensor.

#### - Covert Design

The discreet design make the camera easy to blend into business environment. The customer will feel comfortable without seeing the camera shooting on them.

#### - All-in-one camera system

Users can choose either deploying IP door frame camera standalone or add the camera to the existed surveillance system. The footage can be recorded in the TF card inside the camera. Users don't need to take off memory card to retrieve the footage, They can access the camera remotely over the network connection.

#### - Simple setup.

Users can connect the 2646-62 camera to the network with WIFI. It eliminates the requirement to wire back to a router.

### Typical Application

Home

Retail

Convenience Store

Workshop

Office

and others

## Specification

### Power

Input voltage	+12 VDC
Power consumption	4.5 W (max)

### Video

Sensor type	1/3 inch Type CMOS Sensor
Sensor pixels	1280*960
Sensitivity	1.0 lx (IR off)
Main-stream Resolution	1280*720@25fps
Sub-stream Resolution	4CIF@25fps
Video compression	H.264 MP (Main Profile)
DWDR	ON/OFF
3D DNR	Yes

### Lens

Lens type	3.6 mm pinhole lens
Field of View	H: 72°
Lens mount	Board mounted
Day & Night	Auto

### Connection

Analog video out	N/A
Alarm input (optional)	1 alarm in
Alarm out (optional)	N/A

### Audio (optional)

Audio input	RCA jack connector
Audio output	RCA jack connector
Audio communication	Two-way, full duplex
Audio compression	G.711 (live and recording)

### Local Storage

Memory card slot	Supports up to 128 GB micro SD card (An SD card of Class 8 or higher is recommended for HD recording)
Recording	Continuous recording, Motion/schedule recording

### Software Control

Unit configuration	Via web browser or PC surveillance software
--------------------	---

### Network

Protocols	HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x
Ethernet	N/A
Wireless	IEEE 802.11b/g/n
PoE	N/A

### Mechanical

Dimensions	105*80.5mm
Weight	TBA

### Environmental

Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)