

# 2650-51

## Self Recording IP Smoke Detector Covert Camera



### Key Vaule Highlight

#### - Covert design

The users can have advantages for their investigation by setting up smoke detector camera. Hidden inside the smoke detector housing makes the camera nearly undetectable.

#### -HD Image Detail

The Smoke detector camera can provide image detailed in 4MP HD resolution with its 1/3 inch CMOS sensor.

#### -All-in-one camera system

Users can choose either deploying camera standalone or add the camera to the existed surveillance system. The footage will be recorded into the MacroSD card inside the camera. Users don't need to take off memory card to retrieve the footage. They can access the live and playback remotely over the network connection.

#### -Simple setup

Users only need single cable to carry the power and network to the camera. The power will be separated from the network cable with POE function.

### Typical Application

Home

Retail

Convenience Store

Workshop

Logistics center

and others

## Specification

Power	
Input voltage	+12 VDC or Power-over-Ethernet
Power consumption	6.0 W (max)
Video	
Sensor type	1/3 Type CMOS Sensor
Sensor pixels	2592*1520
Sensitivity	1.0 lx (IR off) 0 lx (IR on)
Main-stream Resolution	2592*1520@25fps; 1920*1080@25fps
Sub-stream Resolution	4CIF@15fps
Video compression	H.264, H.264+, H.265
DWDR	ON/OFF
3D DNR	Yes
Night vision <sup>1</sup>	
IR cut filter	Yes
Lens	
Lens type	3.7 mm pinhole lens
Field of View	H: 76°
Lens mount	Board mounted
Day & Night	Auto ICR Switch
Audio (NOT included)	
Audio input	RCA jack connector
Audio output	RCA jack connector
Audio communication	Two-way, full duplex
Audio compression	G.711 (live and recording)
Local Storage	
Memory card slot	Supports up to 128 GB micro SD card (An SD card of Class 8 or higher is recommended for HD recording)
Recording	Continuous recording, Motion/schedule recording

1. The camera can see the external infra-red, require external infrared illuminator to boost up the night vision.

Software Control	
Unit configuration	Via web browser or PC surveillance software
Network	
Protocols	HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x
Ethernet	10/100 Base-T, auto-sensing, half/full duplex, RJ45
Wireless	IEEE 802.11b/g/n
PoE	IEEE 802.3af compliant
Mechanical	
Dimensions	130*50mm
Weight	TBA
Environmental	
Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)
Ordering Information	
IP Smoke Detector Covert Camera	2650-51