2651-83

AHD Smoke Detector Covert Camera



Key Vaule Highlight

- Covert design

The users can have advances for their investigation by setting up a 2651-83 AHD Smoke Detector Covert Camera. Hidden inside the Smoke Detector housing make the camera undetectable.

- HD Image Detail

The 2651-83 AHD Smoke Detector Covert Camera can provide image detailed in 1.3MP HD resolution with its 1/3 inch CMOS sensor.

- Night Vision

2651-83 AHD Smoke Detector Covert Camera is able to see the external infrared at night with built-in IR cut filter and photocells control.

- Re-use the coxial cable.

The user can re-use existed coaxil cable to ugprade the analog system to HD CCTV with 2651-83 AHD Smoke Detector Covert Camera.

Typical Application

Retail

Convenience Store

Workshop

Logistics center

and others

GOLBONG

Specification

Power	
Input voltage	+12 VDC
Power consumption	4.5 W (max)
Video	
Sensor type	1/3Type CMOS Sensor
Sensor pixels	1280x960
Sensitivity	1.0 lx (IR off)
Resolution	1280x960
Video Output	1 composite video 1 Vpp 75 ohm automatic termination
Day & Night	photocells control
Shutter	Auto (1/50(1/60)s to 1/10,000s)
AGC	Auto
Night vision	
LED	N/A
Lens	
Lens type	3.7mm
Field of View	H: 76°
Lens mount	Board mounted
Day & Night	IR Cut filter
Mechanical	
Dimensions	130*50mm
Weight	ТВА
Environmental	
Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)
Ordering Informat	ion
AHD Smoke Detector Covert Camera	2651-83

GOLBONG

Guangzhou

No.3 East Alley, Guangfeng East Road, Zengchen District, Guangzhou,, 511300, P.R.China

Tel: +86-20-8244-2660 Fax: +86-20-8274-5925 Email: sales@golbong.com

Shenzhen

1/F Block 295, Jiuwei, Xixiang Town, Baoan District, Shenzhen, 518000, P.R.China Tel: +86-755-81465995

Fax: +86-755-81469770 Email::sales@golbong.com

© Golbong Technologies | Data subject to change without notice Cur: en-US, V1, 7 July 2016