

2676-30

4MP 2-Sensor Camera Station with color night-vision



Key Vaule Highlight

- Flexible Coverage

Users can adjust the shooting direction of each sensor, even change the lens to achieve the optimal viewing angle.

- Watching Corridor

Users can deploy 2676-30 camera to monitor the same direction but different distance such as corridor.

- 180 Panoramic View

User can put two sensors together to have 180 degree panoramic view.

- Color night-vision Image

The 2676-30 camera can deliver color night-vision image with extra detail in the low light condition.

- Moving object capturing

2676-30 camera is capable of capturing moving objects and deliver less blurry image which is value for POS area, entrance or exit.

- Saving installation cost

The users can wire single cable and install 2 camera at once. POE function allows one cable to carry the power and network to the camera.

- Working with Regular NVR

The 2676-30 camera can work with regular standalone NVR for footage recording.

- Complete Open

The users can deploy 2676-30 camera with 3rd-party software basing Onvif protocols.

Typical Application

Convenience Store

Headquarter office

Workshop

Logistics

Retail

and others

Specification

Power

Input voltage	+12 VDC or Power-over-Ethernet
Power consumption	15 W (max)

Video

Sensor type	1/2.8 Type SONY Exmor CMOS Sensor
Sensor pixels	1920x1080
Sensitivity	0.01 lx (IR off)
Main-stream Resolution	2 stream 1920x1080@25fps
Sub-stream Resolution	2 stream 4CIF@25fps
Video compression	H.264 MP (Main Profile)
DWDR	ON/OFF
3D DNR	Yes

Night vision

LED	N/A
-----	-----

Lens

Lens type	3.6 mm, Fixed Iris F1.4
Field of View	82 degree x 2
Lens mount	Board mounted
Day & Night	Auto ICR Switch

Connection

Analog video out	N/A
Alarm input (optional)	1 alarm in
Alarm out (optional)	N/A

Audio (optional)

Audio input	RCA jack connector
Audio output	RCA jack connector
Audio communication	Two-way, full duplex
Audio compression	G.711 (live and recording)

Software Control

Unit configuration	Via web browser or PC surveillance software
--------------------	---

Network

Protocols	HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x
Ethernet	10/100 Base-T, auto-sensing, half/full duplex, RJ45
IP address	2 independent IP address
Wireless	N/A
PoE	IEEE 802.3at compliant

Mechanical

Dimensions	Diameter: 122 mm Height: 148 mm
Weight	TBA

Environmental

Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)

Ordering Information

4MP 2-Sensor Camera Station	2676-30
-----------------------------	---------

Guangzhou

No.3 East Alley, Guangfeng East Road,
Zengchen District, Guangzhou., 511300,
P.R.China
Tel: +86-20-8244-2660
Fax: +86-20-8274-5925
Email: sales@golbong.com

Shenzhen

1/F Block 295, Jiuwei, Xixiang Town,
Baoan District, Shenzhen, 518000,
P.R.China
Tel: +86-755-81465995
Fax: +86-755-81469770
Email: sales@golbong.com