3433-29

HD Wide Angle View Camera



Key Vaule Highlight

- Re-use the coxial cable.

The user can re-use existed coaxil cable to upprade the analog system to HD CCTV with 3433-29 camera.

- HD Image Detail

The 3433-29 camera can provide image detailed in 2MP HD resolution with its 1/2.8 inch EXMOR CMOS sensor.

- Discreet design

The discreet design make the camera easy to blend into business environment. The customer will more feel comfortable without seeing the camera shooting on them.

- Night vision

The 3433-29 camera can capture clear image at night with its built-in infrared LEDs.

- Ultra Wide Angle View

Users can deploy 3433-29 camera to cover wide area with activities monitoring.

Typical Application

Hotel

Convenience store

Retail

Home

and others

GOLBONG

Specification

Power	
	142 VDC
Input voltage	+12 VDC
Power consumption	6 W (max)
Video	
Sensor type	1/2.8 Type SONY Exmor CMOS Sensor
Sensor pixels	1920x1080
Sensitivity	0.2 lx (IR off) 0 lx (IR on)
Resolution	1920x1080
Video Output	1 composite video 1 Vpp 75 ohm automatic termination
Day & Night	photocells control
Shutter	Auto (1/50(1/60)s to 1/10,000s)
AGC	Auto
Night vision	
Distance	8 m
LED	12 LED high efficiency array, 850 nm
Lens	
Lens type	2.8mm
Field of View	H: 92°
Lens mount	Board mounted
Day & Night	Auto ICR Switch
Mechanical	
Dimensions	Diameter: 98 mm Height: 63mm
Weight	TBA
Environmental	
Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)
Ordering Information	
1080p Coaxial Analog HD Dome Camera	3433-29

GOLBONG

Guangzhou

No.3 East Alley, Guangfeng East Road, Zengchen District, Guangzhou,, 511300, P.R.China

Tel: +86-20-8244-2660 Fax: +86-20-8274-5925 Email: sales@golbong.com

Shenzhen

1/F Block 295, Jiuwei, Xixiang Town, Baoan District, Shenzhen, 518000, P.R.China Tel: +86-755-81465995

Tel: +86-755-81465995 Fax: +86-755-81469770 Email::sales@golbong.com