

4014-23

P2P WIFI Implement Camera



Key Vaule Highlight

- Point to Point Access

The user can easily connect to 4014-23 camera and access the live or footage with smart phone directly.

- HD Image Detail

The 4014-23 Camera provide image detailed in 1.3MP HD resolution with its 1/3 inch CMOS sensor.

- Macro SD card on-board recording

The footage can be recorded in the TF card inside the camera. Users don't need to take off memory card to retrieve the footage, They can access the footage over smart phone.

- Simple setup.

Power up the camera, it will start recording automatically.

Typical Application

School bus

Truck

Logistics

Van

other Vehicle

Specification

Power	
Input voltage	+12 VDC
Power consumption	6 W (max)
Video	
Sensor type	1/3 Type CMOS Sensor
Sensor pixels	1280x960
Sensitivity	0.5 lx (IR off) 0 lx (IR On)
Main-stream Resolution	1280x960@25fps, 1280x720@25fps
Sub-stream Resolution	4CIF@25fps
Video compression	H.264 MP (Main Profile)
DWDR	ON/OFF
3D DNR	Yes
Night vision	
Distance	10 m
LED	18 LED high efficiency array, 850 nm
Lens	
Lens type	2.8 mm pinhole lens
Field of View	H: 103°
Lens mount	Board mounted
Day & Night	Auto Switch
Connection	
Analog video out	N/A
Alarm input (optional)	1 alarm in
Alarm out (optional)	N/A
Audio (optional)	
Audio input	RCA jack connector
Audio output	RCA jack connector
Audio communication	Two-way, full duplex
Audio compression	G.711 (live and recording)
Local Storage	
Memory card slot	Supports up to 128 GB micro SD card (An SD card of Class 8 or higher is recommended for HD recording)
Recording	Continuous recording, Motion/schedule recording

Software Control	
Unit configuration	Via web browser or PC surveillance software
Network	
Protocols	HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x
Ethernet	N/A
Wireless	IEEE 802.11b/g/n
PoE	N/A
Mechanical	
Dimensions	78*50*50mm
Weight	TBA
Environmental	
Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)
Ordering Information	
P2P WIFI Implement Camera	4014-23

Guangzhou

No.3 East Alley, Guangfeng East Road,
Zengchen District, Guangzhou., 511300,
P.R.China
Tel: +86-20-8244-2660
Fax: +86-20-8274-5925
Email: sales@golbong.com

Shenzhen

1/F Block 295, Jiuwei, Xixiang Town,
Baoan District, Shenzhen, 518000,
P.R.China
Tel: +86-755-81465995
Fax: +86-755-81469770
Email: sales@golbong.com