

## 5440-26

# 60W High Power POE Switch



### Key Vaule Highlight

**- Adding more Cameras with PoE**

The user can add the new PoE cameras to the system with existed network cable.

**- 60W max power sourcing**

The 5440-26 switch can provide 60W max power source in single cable to network camera or PoE extender front-end.

**- Reliable Architecture**

The 5440-26 switch can keep working 24/7 with cooling system.

**- 10/100/1000Mbps network**

The 5440-26 switch can take the challenge from 4K surveillance with its Gigabit ethernet strucutre.

### Typical Application

Retail  
Convenience Store  
Headquarter office  
Workshop  
Logistics  
Home  
and others

## Specification

| Ports                      |  |
|----------------------------|--|
| Number of Ports            | 8 ports (4 ports PoE)  |
| Data Rate                  | 10/100/1000BaseTX  |
| Performance                |  |
| MAC Address                | 4 K  |
| Buffer Memory              | 1.625 M bits   |
| Transmission Method        | Store and Forward  |
| Transmission Media         | 10BaseT Cat. 5 UTP/STP<br>100BaseTX Cat. 5 UTP/STP<br>1000BaseTX Cat. 5 UTP/STP  |
| Filtering/Forwarding Rates | 11.90Mpps  |
| Mechanical Characteristics |  |
| LED Indicators             | Per Port: Link/Act   |
|                            | PoE Act/Status   |
|                            | Power  |
| Electrical Characteristics |  |
| Input                      | 100 ~ 240 V/AC, 50 ~ 60 Hz   |
| Standard                   | 802.3at/af compliant, 60W PoE  |
| PoE Ports                  | 4 Ports  |
| Max. Power Consumption     | 180 W  |
| Connectors                 | Shielded RJ45, EIA 568A and 568B   |
| Network cables             | Shielded category 5 (or higher)  |
| Wiring                     | Data provided over pairs 1/2 and 3/6 for 10/100 Ethernet, over all four pairs for Gigabit Ethernet<br>Power over pairs 1/2 (+), 3/6 (-), 4/5 (+) and 7/8 (-) |
| Dimensions (H x W x D)     | 280*179*45mm   |
| Weight                     | 2.24 kg  |
| Operating Temperature      | 0°C ~ 45°C (32°F ~ 113°F)  |
| Storage Temperature        | -20°C ~ 90°C (-4°F ~ 194°F)  |
| Humidity                   | 10 to 90% RH (non-condensing)  |

| Standards and Regulatory  |  |
|---------------------------|--|
| Standards                 | IEEE-802.3at PoE+ / PSE<br>IEEE 802.3 10BaseT<br>IEEE 802.3u 100BaseTX<br>IEEE 802.3x Flow Control |
| Regulatory                | CE, FCC Class A  |
| Ordering Information      |  |
| 60W High Power POE Switch | 5440-26  |

### Guangzhou

No.3 East Alley, Guangfeng East Road,  
Zengchen District, Guangzhou., 511300,  
P.R.China  
Tel: +86-20-8244-2660  
Fax: +86-20-8274-5925  
Email: sales@golbong.com

### Shenzhen

1/F Block 295, Jiuwei, Xixiang Town,  
Baoan District, Shenzhen, 518000,  
P.R.China  
Tel: +86-755-81465995  
Fax: +86-755-81469770  
Email: sales@golbong.com