

5540-36

PoE Switch 4 Port for PTZ Camera



Description

5540-36 PoE switch is designed for IP CCTV surveillance application. It can handle 1 PoE PTZ camera (30W) plus 3 convenient PoE IP cameras. The PoE+ capability allows the 5540-36 switch to output maximum 30W power in a single port. 2-port Uplink, one is reserved for the NVR recorder. You will be able to connect the NVR to the switch together with the IP cameras. Surge Protection design guarantees the switch can carry unstopping data and power in 24/7.

Typical Application

Retail
Convenience Store
Workshop
Logistics
Home
and others

Specification

Ports	
Number of Ports	4 ports PoE
Data Rate	10/100 BaseTX
Performance	
MAC Address	2K
Jumbo frame	1528K Bytes
Transmission Method	Store and Forward
Transmission Media	10BaseT Cat. 5 UTP 100BaseTX Cat. 5 UTP
Packet buffer	768K/M bit
Bandwidth	1.2Gbps
Mechanical Characteristics	
LED Indicators	Per Port: Link/Act
	PoE Act/Status
	Power
Electrical Characteristics	
Input	48V/1.5A
Standard	802.3at/af compliant
PoE Ports	1-4 port, 10/100Mbps POE Ethernet port
Uplink	5-6 port, 10/100Mbps Ethernet port
Max. Power Consumption	60 W
Connectors	Shielded RJ45, EIA 568A and 568B
Network cables	Shielded category 5 (or higher)
Wiring	Data & Power is provided over pairs 1/2 and 3/6
Dimensions (H x W x D)	120*107*29 mm
Weight	0.396kg
Operating Temperature	0°C ~ 45°C (32°F ~ 113°F)
Storage Temperature	-20°C ~ 90°C (-4°F ~ 194°F)
Humidity	10 to 90% RH (non-condensing)

Standards and Regulatory	
Standards	IEEE-802.3at PoE+ / PSE IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.3x Flow Control
Regulatory	CE, FCC Class A
Ordering Information	
PoE Switch 4 Port	5540-36

Guangzhou

No.3 East Alley, Guangfeng East Road,
Zengchen District, Guangzhou., 511300,
P.R.China
Tel: +86-20-8244-2660
Fax: +86-20-8274-5925
Email: sales@golbong.com

Shenzhen

1/F Block 295, Jiuwei, Xixiang Town,
Baoan District, Shenzhen, 518000,
P.R.China
Tel: +86-755-81465995
Fax: +86-755-81469770
Email: sales@golbong.com